



**GEOCEL**

**2300® Construction Tripolymer Sealant**

- CARB VOC compliant
- Adheres to wet or oily surfaces
- Stays flexible - will not crack
- Superior ultraviolet resistance
- Applies in any temperature
- Paintable - contains no silicone
- 50-year service life
- Available in crystal clear, colors, and specially designed metal roof colors. For a listing of popular metal roofing manufacturers that we match, use the drop down menu below
- Excellent adhesion to most building materials including painted (Kynar®) metal



MBS#	Color	OZ.
66100	Clear	10.3
66101	White	10.3
66102	Gray	10.3
66103	Black	10.3
66104	Brown	10.3
66105	Bronze	10.3
66107	Tan	10.3
66108	Cedar	10.3
66109	Almond	10.3
66115	Driftwood	10.3
66116	Earthtone	10.3
66117	Terra	10.3

**GEOCEL**

**2310® Tripolymer Brushable Sealant**

- Superior Leak Prevention
- Stop Roof Leaks Permanently & Immediately
- Asphalt compatible
- Unlimited repair applications
- Prevents rust and staining
- Crystal clear
- Clear coats copper and other non-ferrous metals
- Paintable



MBS#	Color	Amount
65300	Clear	1 gallon

**GEOCEL**

**3300® Polyurethane Sealant**

- Moisture cure
- Contains no TDI (toluene diisocyanate)
- CARB VOC compliant
- Bonds to most common construction materials without priming



MBS#	Color	OZ.
68101	White	10.3
68102	Gray	10.3
68103	Black	10.3
68104	Medium Bronze	10.3
68105	Bronze	10.3
68106	Limestone	10.3
68107	Tan	10.3
68108	Redwood Tan	10.3
68109	Aluminum Gray	10.3

**SONNEBORN**

**NP1 Caulking Sealant**

**Polyurethane  
 NP-1™**

- Polyurethane Sealant is a one-component high-performance gun-grade moisture-curing polyurethane sealant designed for a wide range of sealing and caulking applications in active exterior joints.
- With 800% elongation, 350 psi tensile and +/- 25% joint movement capability, NP-1 handles most every exterior application.
- NP-1™ requires no mixing and typically bonds to many materials without a primer, including concrete and masonry.
- NP1 dries with a smooth finish and is paintable.



MBS#	Color	Size
NP1GRAY	Gray	10.1 oz.
NP1WHITE	White	10.1 oz.
NP1TAN	Tan	10.1 oz.
NP1MEDBRO	Med. Bronze	10.1 oz.
NP1SB	Special Bronze	10.1 oz.
NP1LIMSTON	Limestone	10.1 oz.
NP1STONE	Stone	10.1 oz.
NP1RWT	RedWood Tan	10.1 oz.

**GEOCEL**

**8125® High Performance Silicone Caulk**

**Acetoxy Cure**

- Excellent adhesion to non-porous surfaces
- 100% silicone
- Meets ASTM C920, TT-S-00230
- FDA/USDA approved
- High modulus, 25% joint movement



MBS#	Color	OZ.
68111	Clear	10.3
68112	White	10.3
68113	Black	10.3

**GEOCEL**

**3500™ Roof Tile Adhesive/Sealant**

- One-part urethane moisture cure sealant
- CARB VOC compliant
- Meets TT-S-00230C, Class A Non-sag, ASTM C920, Type S, Grade NS, Class 25, NT, A & M, CAN/CGSB-19, 13 Canada
- 50-year durability rating
- Both bonding and sealing applications
- Fast set-up, no shrinkage



MBS#	Color	OZ.
35102	Gray	10.3
35103	Black	10.3
35104	Brown	10.3
35107	Tan	10.3
35117	Terra Cotta	10.3



**GEOCEL  
 Mortar Sealant**

- Texturized acrylic sealant
- Looks like mortar
- Water clean-up
- Remains flexible
- Excellent adhesion to most building materials
- Paintable



MBS#	Color	OZ.
36102	Gray	10

**GEOCEL  
 Expanding Foam Sealant**



- Expands 2-1/2 to 3 times to fill large voids and holes
- Fills holes caulk can't

MBS#	OZ.	Pack
43100	12	12 Cans

**GEOCEL  
 2010™ Copolymer Sealant  
 Brushable Elastomeric**


- May be applied at any working temperature
- Stop Roof Leaks Permanently & Immediately
- Exhibits immediate adhesion to most building materials
- May be applied in layers to build up desired sealant thickness
- Semi-self-leveling
- Excellent adhesion to metal, concrete, and wood
- Not asphalt compatible



MBS#	Color	Gallons
60700	Clear/Translucent	1
60701	White	1
60702	Gray	1

**GEOCEL  
 RP-400® Plastic Wet-Dry Surface  
 Roof Cement-Black  
 Brushable**

- Meets ASTM D 4586, Type I
- Asbestos free
- Meets wet application requirements of ASTM D 2822, Type I, Class II
- Works on wet-dry surfaces, even under water
- Remains soft and pliable and resists temperature change
- Resists water immediately



MBS#	Color	Gallons
01101	Black	1

**GEOCEL  
 2315LRF® Fibered Brushable Sealant  
 Leak Repair**

- Stops leaks immediately and permanently
- Adheres to EPDM, TPO, Metal, BUR, and SPF roofing
- Works in wet and icy conditions
- 30-year limited warranty
- Fibered for strength
- Applies at any temperature



MBS#	Color	Amount
69200	Clear	1 gallon
69201	Bright White	1 gallon
69202	Charcoal Gray	1 gallon
69203	Black	1 gallon
69205	Bronze	1 gallon

**GEOCEL  
 1200 Poly Mesh Fabric**

- For use with all brushables

MBS#	Description	Size	Pack
12004	Poly Mesh 4"	4" x 50'	4 Rolls
12006	Poly Mesh 6"	6" x 50'	3 Rolls



**Call us for all your sealant needs.**



**PAINTS**

**General Purpose Spray Paint**

Weekend® Economy Paints are economical, all-purpose enamel paints recommended for touch-up, maintenance and general marking applications.

- Equipped with standard valve
- Dries tack-free in 20 minutes
- Acrylic enamel formulation

Recommended Uses: For use on ceramic, plaster, glass, metal, wood, and most other surfaces.



MBS#	Color	Size
GENWHITE	WHITE	11 oz
GENBLUE	BLUE	11 oz
GENYELLOW	YELLOW	11 oz
GENORANGE	ORANGE	11 oz
GENGREEN	GREEN	11 oz
GENRED	RED	11 oz
GENBLACK	BLACK	11 oz

**PAINTS**

**Red Oxide Primer**

Rust Tough® Aerosols are a rust-preventative acrylic alkyd enamel that offers state-of-the-art corrosion protection. Rust Tough™ provides excellent gloss and color retention, superior durability and one-coat coverage.

Complete coverage with one coat

Dries to touch in 25 minutes; dries to handle in 1 hour

Superior appearance and color retention

Ideal for small touch-up jobs, painting irregular shapes or covering hard-to-reach areas

For both indoor and outdoor use

Tough, high gloss finish resists chipping and peeling

Acrylic enamels and primers are equipped with EZ TOUCH® FANSPRAY® Nozzle

Modified acrylic enamel formulation

Recommended Uses: Steel, aluminum, properly primed metal and wood, structural steel, storage tanks, bar joists, handrails, piping, pipe racks, conveyors, ladders, fencing, machinery, metal doors and marine applications above boot topping. Note: Not recommended for immersion.



MBS#	Color	Size
REDOX	RED OXIDE	12 oz
GREYPRIME	GREY	12 oz

**3M ADHESIVES**

**Spray Adhesives**

**Heavy Duty**

76 Hi-Tack Adhesive - VOCs=71%

- Strong, one-surface bonds
- High temperature resistance
- Low misting, precise spray control
- Variable width spray pattern
- Does not cavitate expanded polystyrene foam
- Bonding carpet, door skins and fabric in van conversions
- Attaching nameplates, pool table fabrics, pool liners, pipe insulation
- Bonding insulation in aircraft interiors and specialty cabinets
- Size: 16.5 ounces; Pack: 12

MBS#
82697-9

**PAINTS**

**Inverted Marking Paint**

When you work you want to be on point. Worksites that need organization, like utilities, excavation sites, construction sites, or surveying, need precision. When you need to make a point with paint, you need a product that will help you be as specific as possible. Krylon Industrial Quick-Mark produces a line that counts with water and solvent based, APWA, and fluorescent inverted paints. You can use our Krylon paints to mark gas, petroleum, oil, roads, water, electrical, sewers, drains, phone and conduit lines, future excavation sites, and temporary survey markings. These paints won't clog, the tip won't fall off with extended use, and will dry-fast and adhere to hot, cold or wet surfaces. These marking paints are VOC and MIR compliant and free of lead.



MBS#	Color	Size
INVWHITE	WHITE	12 oz
INVGREEN	GREEN	12 oz
INVYELLOW	YELLOW	12 oz
INVBBLUE	BLUE	12 oz
INVRED	RED	12 oz
INVORANGE	Orange	12 oz

**PAINTS**

**Cold Galvanizing Spray**

Cold Galvanizing 95 is a complete zinc metal spray which rustproofs any metal surface with thorough protection that lasts for years. It is equivalent to a hot galvanizing treatment as it fuses and adheres to all metal surfaces, stopping corrosion immediately. Zinc used in this product is 95% pure. Coated surfaces can be welded safely without fire or fumes. Resistant to abrasion, cracking or peeling, and oxidation. Heat resistant up to 400°F. Does not contain lead.

- Fuses to metal
- Stops corrosion immediately
- Conforms to military specifications MIL-P-21035 USAF, MIL-P-26915A, MIL-P-46105 for primer coatings and galvanizing repair



MBS#	Color	Size
COLDGALV	Galvanized	12 oz
SILVGALV	Silver	12 oz

**WD-40 CO.**

**Penetrating Lubricant**

- Finds squeaks and lubricates them in hard-to-reach mechanisms
- Silicone-free, no residue
- Protects metal against moisture and corrosive elements with an invisible barrier
- Loosens rusted parts, frees sticky mechanisms and keeps controls and linkages working freely
- Displaces moisture

MBS#	Size	Pack
42060	6 oz.	24
10008	8 oz. Aerosol	12
10011	11 oz. Aerosol	12
10016	16 oz. Aerosol	12
10010	1 gal.	4
10117	5 gal.	1
10118	55 gal.	1
10000	16 oz. Spray Applicator Bottle	4





**CHAMPION CUTTING TOOL**  
**Cutting Fluid & Wax**  
*Brutelube*

Multipurpose cutting and tapping fluid that extends tool life and reduces chip welding. Formulated to cling to your tools for a continuous shield against friction and heat, thus reducing tool costs and work piece scrap. Along with BruteLube Wax, Champion provides a precision finish with closer tolerances on your finished work. They are especially effective on stainless steel, aluminum and many exotic alloys.



MBS#	Description
XLUB-4	4oz.
XLUB-16	16oz.
XLUB-128	1 gallon
XLUB-WAX2	2 oz.
XLUB-WAX16	17 oz.

**JET**  
**AIR TOOL OIL**  
*MARVEL*

- Specially engineered for the care of all piston-type and rotary air tools
- Available in handy 4 ounce bottles with spout caps, and 1 quart cans
- Contains special antioxidants and rust inhibitors
- Insures maximum performance by dissolving gums and sludges that cut down tool speed and reduce power output
- Prevents rust formation
- Provides positive lubrication necessary for smooth starting and longer tool life; will not harm O-rings or seals



MBS#	Desc.
AO-4	4 oz. Air Tool Oil
AO-32	32 oz. Air Tool Oil

**RELTON CORP.**  
**Thread Cutting Oils**  
*ReadyTo Cut*  
**TCO-14™**

- Ready to cut clean, smooth threads on all pipe materials
- Extreme-pressure additive for anti-weld characteristics
- Excellent protection of tools and machined parts against corrosion
- Contains anti-mist component for a healthier work environment
- Shipping weights are approximate and rounded to the nearest pound
- TCO-16 - Operationally interchangeable with TCO-14 (Dark)
- Case Qty: 4



MBS#	Description
01G-TCO14	1 Gallon Bottles, Dark
01G-TCO16	1 Gallon Bottles, Light

**RELTON CORP.**  
**Band-Saw Cutting Fluid**  
**REL SAW**

- Improves blade life
- Stable over a wide variety of water conditions
- Promotes cleaner-running machines compared to soluble oils
- Reduces machine wear
- Long emulsion life
- Contains rust and corrosion inhibitors
- Fortified with boundary lubricants



MBS#	Description
01G-RS	1 Gallon Bottles
05G-RS	5 Gallon Pail
55G-RS	55 Gallon Drum

**CUTTING FLUID**  
**Uni-Cool**  
**Sawing & Cutting Fluid**

Coolant, Lubricant, Rust Inhibitor specially formulated for stationary band saws. Keeps your machine running clean and improves the life of your blades.

- The perfect solution for your stationary Band Saw



MBS#	Description
Uni5gal	5 gallon bucket
Uni55gal	55 gallon drum

**VENTURE TAPE**  
**Double Coated Polyester Tape**  
**514CW®**  
**WMP-VR**

Venture Tape 514CW is a double coated polyester film tape coated on both sides with an aggressive acrylic pressure sensitive adhesive (PSA). A high performance splicing tape specifically designed for splicing in continuous web processes, Venture Tape 514CW is especially suitable for corrugated paper applications.




MBS#	Size
514CW®	1-1/2"x 180'

VENTURE TAPE

**Medical Grade Double Coated Polyester  
 Tape**  
**3604MHD**  
**WMP-VR**

A 1 mil (25micron) thick polyester film coated on both sides with an aggressive medical grade acrylic adhesive system (M 104) that delivers high tack, high peel, and high shear strength. This product has excellent adhesion to paper, films, and natural and synthetic fabrics. The low outgassing adhesive has excellent temperature resistance and, under federal guidelines, is not considered a primary skin irritant tape.



MBS#	Size
3604	1- 1/2"x180'

VENTURE TAPE

**Polypropylene Face Tape**  
**1537CW®**  
**WMP-VR**

A 3 x 4 tri directionally reinforced, UL listed, white or black polypropylene/scrim/kraft lamination. Coated with a special cold weather acrylic pressure sensitive adhesive system, this is the ultimate in cold weather tapes combining superior quick stick at normal temperatures with superior low temperature performance down to 10oF ( 12oC). Better in humid as well as hot conditions.  
 Primary Use: Closure system and vapor seal on Lamtec WMP VR insulation.



MBS#	Size
1537CW	3"x50 yds.

VENTURE TAPE

**Aerospace Grade Tape**  
**1163**  
**WMP-VR**

Venture Tape 1163 is a double coated polyester (PET) film tape coated on both sides with an extremely acrylic pressure sensitive adhesive (PSA). A high performance aerospace grade tape specifically designed for the most demanding bonding applications, Venture Tape 1163 provides permanent bond on foams, plastics, metals, and composite materials subjected to a broad range of environmental conditions.



MBS#	Size
1163	1" x 180'

VENTURE TAPE

**Vinyl Seaming Tape**  
**460**  
**WMP-VR**

Venture Tape 460 is a 3.2 mil embossed vinyl coated with an aggressive acrylic pressure sensitive adhesive. Specifically designed for use as a seaming tape for vinyl faced fiberglass insulation, Venture Tape 460 applies easily and excels in demanding temperature and humidity applications, providing superior performance and durability over a wide range of conditions.  
 Primary Use: Seaming vinyl faced fiberglass insulation in metal buildings and for water heater blanket insulation.



MBS#	Size
460	3"x 50yds

VENTURE TAPE

**VRR-50 Metal Building  
 Facing Tape**  
**1567CW®**  
**WMP-VR**

A triple ply laminate of a white polypropylene film with a metalized polyester film backing and fiberglass scrim.  
 Primary Use: Closure system and vapor seal on Alpha VRR 50 facing.



MBS#	Size
1567CW®	3"x50yds

VENTURE TAPE

**Heavy Duty FSK Facing Tape**  
**1549CW®**  
**WMP-VR**

A flame resistant vapor barrier facing material consisting of .00035 aluminum foil, a blend of fiberglass and polyester yarn reinforcement, and 30 lbs kraft paper laminated together with a flame resistant adhesive. A vapor barrier coating is applied on the aluminum foil to obtain abuse resistance and maintain a consistent 0.02 Perm WVTR. The tape conforms well to both fibrous duct board and blankets. Coated with a special cold weather acrylic pressure sensitive adhesive system that combines superior quick stick at normal temperatures with superior low temperature performance, this is the ultimate in cold weather tapes. Recommended for use at elevated temperatures also.  
 Primary Use: Closure system and vapor seal on FSK faced metal building insulation.



MBS#	Size
1549CW	3"x50yds



**HARDCAST-CARLISLE**  
**ALUMA-GRIP**  
**Roof Patch Tape**  
**701**

ALUMA-GRIP 701 is a HEAVY DUTY pressure sensitive duct joint rolled sealant. ALUMA-GRIP provides an aggressive water resistant grip to most surfaces including sheet metal, duct board, flex duct, PVC coated duct, and duct wrap vapor barriers. ALUMA-GRIP is suitable for subgrade application on PVC coated duct.



MBS#	Width (in.)	Length
304080	4	50 ft.
304081	6	50 ft.
304082	9	50 ft.
304077	12	50 ft.

**GENERAL TAPES**  
**Duct Tape**

Duct Tapes are made from Polyethylene-coated cloth with a natural rubber resin adhesive. Tape will conform well to irregular surfaces, and will not twist or curl during application. Excellent water and abrasion resistance. Tape is hand-tearable (tears evenly across web.) Used as a quality waterproof packaging tape for export shipments; for splicing, vinyl repair, protecting, and bundling; for ductwork sealing and seaming; and for color coding.



MBS#	Size (width x length)
1501	2inx60yds
1500	3inx60yds

**GENERAL TAPES**  
**Electrical Tape**

Electrical tape is a type of tape used to insulate electrical wires and other material that conduct electricity. It can be made of many plastics, but vinyl is most popular, it stretches better, giving a more effective and longer lasting insulation.



MBS#	Size (width x length)
ELETAPE-WHITE	3/4inx60ft
ELETAPE-BLACK	3/4inx60ft
ELETAPE-RED	3/4inx60ft
ELETAPE-GREEN	3/4inx60ft

**GENERAL TAPES**  
**Masking Tape**


Masking tape is typically used in painting project to protect surfaces from unwanted paint coverage. Glass window panes, trim, and ceilings can all be "masked off" to make paint application on adjoining surfaces easier. Inexpensive and relatively easy to use, masking tape is ideal for these types of projects. You simply line up the side of the tape with the edge of the area that you're painting, press the tape down securely, and paint next to it. After the paint dries, it is best to remove the tape at a sharp 90 degree angle to prevent chipping.



MBS#	Size (width x length)
MASKTAPE1	1inx60yds
MASKTAPE2	2inx60yds

**GENERAL TAPES**  
**Butyl Tape**

Butyl tape is a rubber based product that's use is limited only by ones imagination. It is extensively used in the Automotive, roofing, Flooring, industrial, construction and air-conditioning industries. Butyl tape not only has long lasting waterproofing properties, but has excellent anti-vibration properties as well. Butyl sealant is non-hazardous and may be used on most pipes and flanges. It is non-toxic and may be used in the food industry



MBS#	Size (width x length)	QTY PER CASE
007597	1/2x1/8x35'	40 rolls
006797	1/2x3/32x50'	20 rolls
11397	1"x3/32x50'	10 rolls
066097	2-1/2"x50'	3 rolls
011197	1"x1/8x40'	12 rolls
005697	3/8x3/32x50'	24 rolls
009897	3/4x3/16x25'	14 rolls
<b>Double Bead</b>		
10397	7/8x3/16x25'	24 rolls
<b>Triple Bead</b>		
013597	2-1/2'X3/16X20	6 rolls

**Call us for all your tape needs.**



3M ELECTRICAL PRODUCTS

**Splicing Tapes**

**23 Rubber**

**Scotch®**

Scotch®23 electrical tape is a highly conformable, self-fusing Ethylene Propylene Rubber (EPR) - based, high-insulating voltage tape. Scotch® 23 has a "snakeskin" linear that is easily removed as the tape is applied.

- No linear
- Excellent thermal dissipation
- Highly conformable; Makes job easier
- More stable splices; High quality moisture seal
- Saves time, lower installed cost; Provides longer cable life, reduces life cycle cost
- Eliminates call-backs

Description: High & low voltage insulating, self-fusing rubber tape, Tape Thickness: 30 mil, Temp. Rating: Continuous: 194°F (90°C) Short Term: 266°F (130°C), Typical Applications: Primary electrical insulation for splicing all solid dielectric cables through 69 kV., Specs./ Certifications and Listings: HH-I-3825B ASTM D-4388, Type I, II & III, Size: 3/4 in. x 30 ft. (19 mm x 9,1 m), Inner Unit Pack: 1/box, Case Qty: 50 rolls

**MBS#**

23

3M ELECTRICAL PRODUCTS

**Inline Resin Splice Kits**

**82-A Series**

**Scotchcast™**

Use this to insulate and seal single conductor, unshielded cable splices through 5 kV and multiple conductor cables through 1 kV. The 82-A series is UL listed 486D, file no. E102356. Each kit makes one splice. Nonshielded dry cable, 5 and 8 kV, nonshielded wet or dry cable, 5 and 8 kV, single conductor cable to 1000 volt, multiple conductor, to 1000 Volt, cable.

Inner Pack: 1 per box

Case Qty.: 10

MBS#	Max Cable O.D. in. (mm)	Max Connector O.D. in. (mm)	Conductor Size	
82A	0.750 (19)	0.406 (10)	10-2 AWG (6 - 30 sq. mm)	BBMJAA24490MQ82A5
82A1	0.625 (16)	0.406 (10)	Up to 2 AWG (30 sq. mm)	BBMJAA24490MQ82A110
82A2	1.000 (25)	0.625 (16)	2-3/0 AWG (35 - 80 sq. mm)	BBMJAA24490MQ82A215
82A3	1.563 (40)	1.000 (25)	3/0 AWG-400 kcmil (95 - 200 sq. mm)	BBMJAA24490MQ82A320

**Check us out on line at [www.mbs-tools.com](http://www.mbs-tools.com)**